

Industrial IR³ Infra-Red Flame Detector

IFD-E



Features

- ▶ Unaffected by convection currents, draughts or wind and solar-blind
- ▶ Tolerant of fumes, vapours, dust and mist
- ▶ Responsive to a flame more than 25m away
- ▶ Selectable response speed
- ▶ Class 1 performance as defined in BS EN54-10:2002 (on the high sensitivity setting)
- ▶ Optical self-test

Description

Model IFD-E is an IR³ flame detector designed for use where open flaming fires may be expected and responds to the light emitted from flames during combustion.

The detector discriminates between flames and other light sources by responding only to particular optical wavelengths and flame flicker frequencies. This enables the detector to avoid false alarms due to such factors as flickering sunlight. Ideal for the detection of flames from the burning of Aviation Fuels (kerosene), Butane, Grain & Feeds, Hydrogen, Paper, Natural Gas, Petrol (gasoline) etc.

Specification

Ordering codes	IFD-E IFD-MB (Stainless Steel Mounting Bracket)	
Operating voltage	14 - 30Vd.c.	
Alarm Current (selected via by DIL switches)	3 ~ 28mA	
Test Signal Voltage	14 to 30Vd.c.	
Relay Contact Ratings	Current	1.0A (max)
	Voltage	50Vd.c. (max)
	Power	30W (max) (resistive loads only)
Power Up Time	2 seconds (max)	
Field of View	90° min. Cone	
Range	Class 1 - 0.1m ² n-heptane at 25m Class 3 - 0.1m ² n-heptane at 12m	
Operating Wavelength Band	IR (0.75 ~ 2.7µm)	
Operating temperature range	-10°C to + 55°C	
Storage temperature range	-20°C to + 65°C	
Maximum humidity	95% RH - Non condensing (at 40°C)	
Ingress Protection Rating	IP65	
Colour / Case Material	Blue / Die-Cast Zinc Alloy (ZA12)	
Weight (Kg) / Height / Width / Depth (mm)	2 / 142 / 108 / 82	

This product is not suitable for use in Intrinsically Safe areas
See model IFD-E(IS)

Hochiki Europe (UK) Ltd. reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Hochiki Europe (UK) Ltd. to be a complete and up-to-date description.